

CBS-2021eP
EXTRACTOR® Brewer Series



CBS-2021eP with
 LUXUS® L3D-05
 half gallon dispenser
 (Serving stand not shown)



Cascading Spray Dome

Pulse-Brew Intermittent Spray Shower technology with programmable brew volume • brew time • bypass • pre-wet percent • pre-wet delay • drip delay

FETCO's Cascading Spray Dome (CSD) is the latest breakthrough in extraction technology. The CSD's compact design provides the same full and even saturation as the large sprayhead of the EXTRACTOR® line plus it is easy to remove, clean and replace.

- New Cascading Spray Dome for even & full extraction.
- Compact, stylish design.
- Brews directly into 1/2 gallon LUXUS® Thermal Dispenser.



CBS-2021eP with
 1.9L Bowl Server

FETCO® equipment does not contain mercury, lead or fiberglass. Instead we use solid state relays, stainless steel fittings and insulation that do not contain harmful materials.



Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	.25	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
21	8 3/4	17.0	17	23.3

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour	
							<i>cold water</i>	<i>hot water</i>
US and Canada								
E20016P	1x2.1 KW	100/130	1	2+G	3.2	14.9/19.2	8.0	8.0
EXPORT								
E20026P	1x3.2 KW	208/240	1	2+G	3.2	11.7/14.0	8.0	8.0

Specifications subject to change without notice.

