

BUNN®

12 Cup Automatic Coffee Brewer with 3 Lower Warmers

Features

12 Cup Automatic Coffee Brewer

- Brews 3.8 to 6.8 gallons of perfect coffee per hour.
- All stainless steel construction.
- Hot water faucet and pourover feature on all models.
- Model CWTF35-4 has three lower left warmers, one upper warmer.
- SplashGard® funnel deflects hot liquids away from the hand.
- International electrical configurations available.



*Model CWTF15-3**
(3 lower warmers)
(decanter not included)
Dimensions: 17" H x 16" W x 17.7" D

** International models may vary in appearance.*

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-17-TL
Product No. : 30200.1000
Dimensions:
12⁷/₁₆" H x 2¹/₂" W x 3" D
31.6 cm H x 6.35 cm W x 7.62 cm D

Easy Clear® ED-17-TL
Product No. : 30201.1001
Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.
20.95 cm H x 5.87 cm Dia.

Paper Filter Pack
Product No. : 20115.0000
Packed per case: 1,000
Dimensions: 4¹/₄" Base x 2³/₄" Sidewall
10.8 cm Base x 6.98 cm Sidewall



Easy Pour® black decanter
Product No. : 06100.0101
Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



**1GPR SS Portable Server
on an RWS1 Warmer**
1GPR Product No. : 12487.0001*
RWS1 Product No. : 12203.0010
**Also available with side handles or black decor.*



ITEM#

PROJECT

DATE

**International
Model**

CWTF35

Model

*CTF15-3
CWT15-3
CWTF15-3
CWTF20-3
CWTF35-3
CWTF35-4*

BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CWT15-3	12950.0112	120	15	1320	1800	3.9 gal./hr.	6.3	32 lbs. (14.5 kg)	Yes
CWTF15-3	12950.0212	120	15	1320	1800	3.9 gal./hr.	6.2	35 lbs. (15.9 kg)	Yes
CWTF15-3*	12950.0216	120	15	1320	1800	3.9 gal./hr.	6.3	36 lbs. (16.4 kg)	Yes
CWTF20-3	12950.0232	120	20	1800	2400	5.5 gal./hr.	6.3	35 lbs. (15.9 kg)	No
CWTF35-3	12950.0252	120/240	17	3500	4100	6.8 gal./hr.	6.3	35 lbs. (15.9 kg)	No
CWT35-4**	12950.0280	120/240	17	3500	4100	6.8 gal./hr.	6.3	33 lbs. (15.0 kg)	No
CWTF35-4**	12950.0313	120/240	15.4	3500	3700	6.8 gal./hr.	6.3	36 lbs. (16.4 kg)	No

*Stainless steel funnel **3 lower left warmers, one upper.

Electrical: Model 15 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.
 Model 20 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.
 Model 35 requires 3-wires plus ground service rated 120/208 or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male flare fitting.

