

Features

Automatic CDBC Coffee Brewers

- Larger 200 oz. tank provides back-to-back brewing capacity.
- Improved brewing system has better temperature accuracy.
- Adjusts automatically to varying water pressure.
- Quicker install saves up to 30 minutes. Pot level, cold brew lock-out and tank temperature set easily from advanced touch pad on front of machine.
- Faster field repairs and quick problem diagnostics by phone; built-in electronic sensors feed back information on brewer malfunctions.
- Insures coffee brew quality with cold brew lock out capability.
- SplashGard® funnel deflects hot liquids away from the hand.
- Coffee extraction controlled with pre-infusion, Pulse Brew™ and digital temperature control.



*Model CDBCF
(2 top warmers)
(decanters not included)*
Dimensions:
18.9" H x 8.25" W x 17.8" D



*Model CDBCF
(3 lower warmers)
(decanters not included)*
Dimensions:
17" H x 16" W x 17.7" D

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-17-TL
Product No. : 30200.1000
Dimensions:
12⁷/₁₆" H x 2¹/₂" W x 3" D



Easy Clear® ED-17-TL
Product No. : 30201.1001
Dimensions: 8¹/₄" H x 2⁵/₁₆" Dia.

Paper Filter Pack
Product No. : 20115.0000
Packed per case: 1,000
Dimensions: 4¹/₄" Base x 2³/₄" Sidewall



Easy Pour® black decanter
Product No. : 06100.0101
Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



1GPR SS Portable Server on an RWS1 Warmer
1GPR Product No. : 12487.0001*
RWS1 Product No. : 12203.0010
**Also available with side handles or black decor.*



ITEM#

PROJECT

DATE

Line

*CDBCF15 (2 top)
CDBCF15 (3 lower)
CDBC35 (3 lower)
CDBCF35 (3 lower left)
CDBCF35 (3 lower right)*

BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CDBCF15 (3 lower)	28800.0100	120	15	1425	1800	4.5 gal./hr.	6.3	31 lbs. (14.1 kg)	Yes
CDBCF15 (2 top)	28800.0101	120	15	1425	1800	4.5 gal./hr.	4.0	27 lbs. (12.3 kg)	Yes
CDBCF35 (3 lower)* ^b	28800.0113	120/240	16.7	3500	3850	8.5 gal./hr.	6.3	32 lbs. (14.6 kg)	No
CDBC35 (2 top)	28800.0107	120/240	16.7	3500	3850	8.5 gal./hr.	3.7	26 lbs. (11.8 kg)	No
CDBC35 (3 lower)* ^{†b}	28800.0114	120/240	16.7	3500	3850	8.5 gal./hr.	6.3	32 lbs. (14.6 kg)	No
CDBCF35 (2 top) ^b	28800.0115	120/240	16.7	3500	3850	8.5 gal./hr.	3.7	27 lbs. (12.3 kg)	No

*Models have a stainless steel funnel. †Model has lower warmers on the left side of brewer and has no hot water faucet. ^bModel has black decor.

Electrical: 120 volt, 15 amp. models require 2-wires plus ground service rated 120V, single phase, 60 Hz.
120/240 volt models require 3-wires plus ground service rated 120/240V, single phase, 60 Hz.
An internal terminal block is configured for connection to a 3-wire plus ground.

Plumbing: 20-90 psi (138-621 kPa). Machines supplied with 1/4" male flare fitting. Twin models supplied with 3/8" male flare fitting.

