

Features

Dual Coffee Brewer

- Brews 16.3 to 18.9 gallons of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon batches.
- Adjustable bypass ensures perfect coffee regardless of batch size.
- Hot water faucet does not affect brew level.
- Electronic timer insures fast set up and accurate brew levels.
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- 1.5GPR portable server (included) has a patented Safety-Fresh® brew-through lid with vapor seal and spill protection.
- SplashGard® funnel deflects hot liquids away from the hand.
- International electrical configurations available.



*Model Dual®
with two 1.5GPR's**

Dimensions: 29.3" H x 18" W x 22.2" D

** International models may vary in appearance.*

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-11-TL

Product No. : 30344.1001

Dimensions:

15⁷/₈" H x 3⁵/₈" W x 4¹⁷/₃₂" D

40.32 cm H x 9.21 cm W x 11.51 cm D

Easy Clear® ED-11-TL

Product No. : 30244.1001

Dimensions:

14³/₁₆" H x 5¹/₁₆" W x 5¹/₁₆" D

31.0 cm H x 12.86 cm W x 12.86 cm D



Single/Dual Filter Pack

Product No. : 20100.0000

Packed per case: 500

Dimensions: 5¹/₄" Base x 3³/₄" Sidewall

10.8 cm Base x 9.52 cm Sidewall



1.5GPR Safety-Fresh® portable server with bail handles & RWS1 warming stand.

1.5GPR

Product No. : 20950.0002

Dimensions:

10¹/₄" H x 6³/₄" W x 12⁵/₈" D

26.0 cm H x 17.2 cm W x 32.1 cm D

Depth=10¹/₄" w/o guard

26.0 cm w/o guard

Depth=12³/₄" with guard

32.38 cm w/ guard

Width=7⁷/₈" without handle

19.68 cm w/o handle

Width=7⁵/₈" with handle

19.37 cm w/ handle



RWS1 Product No. :

12203.0010

Dimensions: 7.5" H x 8¹/₄" W x 9¹/₃" D

19.05 cm H x 20.96 cm W x 23.62 cm D

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

International Model

Dual

Model

Dual

BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703

Phone

800-637-8606

217-529-6601

Fax

217-529-6644

Technical Services

800-286-6070

Internet

<http://www.bunnomatic.com>

Western Regional Office

16431 Carmenita Road,
Cerritos, California 90701

Phone

562-926-0764

Fax

562-926-0858

Canadian Office

280 Industrial Parkway South
Aurora, Ontario, L4G 3T9

Phone

905-841-2866

Fax

905-841-2775

Patents Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Thermostat	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
Dual†*	20900.0008	120/208	28.8	2 @ 2850	5990	Mechanical	16.3 gal./hr.	12.0	92 lbs. (41.8 kg)	No
Dual**	20900.0010	120/208	28.6	2 @ 2850	5950	Mechanical	16.3 gal./hr.	12.0	94 lbs. (42.7 kg)	No
Dual**	20900.0011	120/240	28.7	2 @ 3300	6850	Mechanical	18.9 gal./hr.	12.0	95 lbs. (43.1 kg)	No

All include Safety-Fresh® server with additional orange faucet handle and decal for decaf service.

† Model 20900.0008 has a plastic funnel. The other models listed include stainless steel funnels

* One setting. ** Three settings.

Electrical: 120/208V or 120/240V models require 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (69-621 kPa). Supplied with 1/4" (6.4 mm) male flare fittings.

