

Features

Coffee brewers with portable servers

- Brews 16.3 to 18.9 gallons (61.7 to 71.5 L) of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.8 L) batches.
- Patented server heat control automatically shuts off once target temperature is reached. Can be set to 175°-190°F (79.4-87.8°C).
- Electronic grinder interface instructs grinder on exact amount of coffee for selected brew batch size.
- Remote 1 or 2 server docking stations for additional satellite coffee serving.
- Safety-Fresh® patented brew-through lid with vapor seal and spill prevention.
- Variable batch selector knob lets you brew large batches or small servings.
- International electrical configurations available.



*Model Dual SH with
1.5 gallon SH Servers*
(servers sold separately)*

Dimensions: 35.8" H x 18" W x 22.2" D
(91 cm H x 45.7 cm W x 56.4 cm D)

* International models may vary in appearance.

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

Easy Clear® EQ-11-TL

Product No. : 30344.1001

Dimensions:

15 7/8" H x 3 5/8" W x 4 17/32" D

40.32 cm H x 9.21 cm W x 11.51 cm D

Easy Clear® ED-11-TL

Product No. : 30244.1001

Dimensions:

14 3/16" H x 5 1/16" W x 5 1/16" D

31.0 cm H x 12.86 cm W x 12.86 cm D

Single/Dual Filter Pack

Product No. : 20100.0000

Packed per case: 500

Dimensions: 12 3/4" overall x 5 1/4" base

32.4 cm overall x 10.8 cm Base



SH Server

Product No. : 27850.0001

Two Position Drip Tray

Product No. : 27150.0000



1.5 gallon SH Servers on 2SH Stand with dual drip tray (optional)

ITEM#

PROJECT

DATE

International Model

Dual SH

Model

Dual SH

BUNN®

Corporate Offices

1400 Stevenson Drive
Springfield, Illinois 62703

Phone

800-637-8606

217-529-6601

Fax

217-529-6644

Technical Services

800-286-6070

Internet

<http://www.bunnomatic.com>

Western Regional Office

16431 Carmenita Road,
Cerritos, California 90701

Phone

562-926-0764

Fax

562-926-0858

Canadian Office

280 Industrial Parkway South
Aurora, Ontario, L4G 3T9

Phone

905-841-2866

Fax

905-841-2775

Patents Apply



Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
Dual SH Brewer	27900.0001	120/208	28.9	2 @ 2850	5900	16.3 gal./hr.	13	90 lbs. (40.9 kg)	No
Dual SH Brewer†	27900.0008	120/208	28.9	2 @ 2850	5900	16.3 gal./hr.	13	91 lbs. (41.3 kg)	No
Dual SH Brewer	27900.0002	120/240	29.1	2 @ 3300	6800	18.9 gal./hr.	13	91 lbs. (41.3 kg)	No
Dual SH Brewer*	27900.0020	120/208	29.1	2 @ 3300	6800	18.9 gal./hr.	13	91 lbs. (41.3 kg)	No
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1½ gal.	2.2	17 lbs. (7.7 kg)	No
SH Server(1.75 gal.)	27850.0002	n/a	n/a	n/a	n/a	1¾ gal.	2.2	18 lbs. (8.2 kg)	No
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1½ gal.	2.2	18 lbs. (8.2 kg)	No
1SH Stand	27825.0000	120	.8	n/a	90	Holds 1 SH Server	1.7	13 lbs. (5.9 kg)	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	Holds 2 SH Servers	2.8	22 lbs. (10.0 kg)	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	Holds 2 SH Servers	2.8	22 lbs. (10.0 kg)	Yes

†Model has recovery booster. *Models have black decor.

Note: Soft Heat® Brewers and Servers are boxed and shipped separately. All brewers have mechanical thermostats.

Electrical: Brewer is 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60Hz.

Plumbing: 20-90 psi (69-621 kPa). Machine supplied with ¼" (6.4 mm) male fitting.

