

## Features

### BrewWISE® Brewing System

- Three batch size capability.
- Stores individual coffee and flavor profiles using adjustable water volume, bypass percentage, Pulse-Brew, and pre-infusion timing
- Operate any combination of equipment error-free with wireless brewer-grinder interface via Smart Funnel.
- Reduce accidents with safety features that decrease hot splashes from funnel, eliminate brewing when funnel or server is not present.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Consistently brew perfect coffee using Digital Brewer Control with BUNN patented Pulse-Brew.
- Simplify installation and calibration by creating your own recipe cards and dedicated funnels with the BrewWISE Recipe Writer (# 34444.0000) on your PC (*Windows® compatible*).



*Model Dual SH DBC with  
1.5 gallon SH Servers  
(servers sold separately)*

Dimensions: 35.8" H x 18" W x 22.2" D

## Related Products

For current specification sheets and other information, go to [www.bunnomatic.com](http://www.bunnomatic.com).

BUNN recommends the use of our Easy Clear® Water Quality Systems and BUNN paper filters to assure perfect taste.

**Easy Clear® EQ-11-TL**  
Product No. : 30344.1001  
Dimensions:  
15<sup>7</sup>/<sub>8</sub>" H x 3<sup>5</sup>/<sub>8</sub>" W x 4<sup>17</sup>/<sub>32</sub>" D



**Easy Clear® ED-11-TL**  
Product No. : 30244.1001  
Dimensions:  
14<sup>3</sup>/<sub>16</sub>" H x 5<sup>1</sup>/<sub>16</sub>" W x 5<sup>1</sup>/<sub>16</sub>" D

**Single/Dual Filter Pack**  
Product No. : 20100.0000  
Packed per case: 500  
Dimensions: 5<sup>1</sup>/<sub>4</sub>" Base x 4<sup>1</sup>/<sub>4</sub>" Sidewall



### BrewWISE® Recipe Writer (BRW)

Product No.: 34444.0000  
Dimensions:  
2<sup>3</sup>/<sub>16</sub>" H x 6<sup>3</sup>/<sub>8</sub>" W x 9<sup>1</sup>/<sub>2</sub>" D



**Recipe Card** - Program a recipe to be used on brewer or grinder.  
Product No.: 34447.0000

**Ad Card** - Program a message to appear on the brewer's display.  
Product No.: 34448.0000

### G9-2T DBC

Product No.: 33700.0000  
• Grinder holds 6 pounds each of regular and decaf or specialty beans.



BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

## International Model

*Dual SH DBC*

## Models

*Dual SH DBC*

## BUNN®

**Corporate Offices**  
1400 Stevenson Drive  
Springfield, Illinois 62703  
**Phone**  
800-637-8606  
217-529-6601  
**Fax**  
217-529-6644  
**Technical Services**  
800-286-6070  
**Internet**  
<http://www.bunnomatic.com>

**Western Regional Office**  
16431 Carmenita Road,  
Cerritos, California 90701  
**Phone**  
562-926-0764  
**Fax**  
562-926-0858

**Canadian Office**  
280 Industrial Parkway South  
Aurora, Ontario, L4G 3T9  
**Phone**  
905-841-2866  
**Fax**  
905-841-2775

Patents Apply



## Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
Dual SH DBC	33500.0000	120/240	29.1	2@3300	6800	18.9 gal/hr	13	90 lbs. (40.8 kg)	No
Dual SH DBC†	33500.0001	120/240	29.1	2@3300	6800	18.9 gal/hr	13	90 lbs. (40.8 kg)	No
Dual SH DBC*	33500.0004	120/240	29.1	2@3300	6800	18.9 gal/hr	13	90 lbs. (40.8 kg)	No
G9-2T DBC	33700.0000	120	9.4	n/a	n/a	n/a	5.1	66 lbs. (29.9 kg)	Yes
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1½ gal.	2.2	17 lbs. (7.7 kg)	No
SH Server(1.75 gal.)	27850.0002	n/a	n/a	n/a	n/a	1¾ gal.	2.2	18 lbs. (8.2 kg)	No
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1½ gal.	2.2	18 lbs. (8.2 kg)	No
1SH Stand	27825.0000	120	.8	n/a	90	Holds 1 SH Server	1.7	13 lbs. (5.9 kg)	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	Holds 2 SH Servers	2.8	22 lbs. (10.0 kg)	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	Holds 2 SH Servers	2.8	22 lbs. (10.0 kg)	Yes

†Model has funnel lock system. \*Models have black decor. **Note:** Soft Heat® Brewers and Servers are boxed and shipped separately.

**Electrical:** Brewer is 3-wires plus ground service rated 120/208V or 120/240V, single phase, 60Hz.  
Grinder is 2-wires plus ground service rated 120V, 60Hz, circuit required, ¾ HP motor.

**Plumbing:** 20-90 psi (69-621 kPa). Machine supplied with ¼" (6.4 mm) male fitting.

