

Features

Gourmet Juice® System

- Narrow cabinet width (9 3/4") conserves counter space
- One dispenser delivers both frozen and ambient products increasing profits by lowering costs
- Drink consistency assured with high-velocity, vortex injection valve design.
- Quick dispense with 1.5 to 2 ounces per second flow rate
- 8" cup clearance accommodates most juice containers
- 10 lb. ice bank assures cold product
- Available with lighted and unlighted displays
- Advanced concentrate pump designed for easy setup, accuracy and durability.
- Superior sanitation control with added rinse-water valve port that can be connected to a hot water line.
- Modular dispense and refrigeration systems make service fast and simple.
- Smart electronics prompt for rinsing and provide semi-automatic sanitizing program for easy cleaning.



Model JDF-2

Dimensions: 33"H x 9.75"W x 25.4"D

ITEM#

PROJECT

DATE

Model

JDF-2

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

Modular compartment design, allows easy access to concentrate.

Both push-button and portion-control dispense available. Portion-control model assures accurate serving size.

Lighted display option available to sell more juice.



Model JDF-2

BUNN recommends the use of our Easy Clear® Water Quality Systems to assure perfect taste.

Easy Clear® EQ-11-T

Product No.: 30321.1000 (manifold)
30331.1002 (cartridge)

Dimensions:
15 7/8" H x 3 5/8" W x 4 17/32" D

Easy Clear® ED-11-T

Product No.: 30221.1000 (manifold)
30231.1002 (cartridge)

Dimensions:
14 3/8" H x 5 1/8" W x 5 1/8" D



BUNN®

Corporate Offices
1400 Stevenson Drive
Springfield, Illinois 62703
Phone
800-637-8606
217-529-6601
Fax
217-529-6644
Technical Services
800-286-6070
Internet
<http://www.bunnomatic.com>

Western Regional Office
16431 Carmenita Road,
Cerritos, California 90701
Phone
562-926-0764
Fax
562-926-0858

Canadian Office
280 Industrial Parkway South
Aurora, Ontario, L4G 3T9
Phone
905-841-2866
Fax
905-841-2775

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

Patents
Apply



Dimensions & Specifications

Model	Product #	Volts/Hz	Amps	Capacity	Dispense	ft ³	Shipping Weight	Cord Attached
JDF-2*	34700.0000	120/60	15	2 (12 oz.) drinks/min**	push button	8.7	110 lbs.	Yes
JDF-2*	34700.0001	120/60	15	2 (12 oz.) drinks/min**	portion-control	8.7	110 lbs.	Yes
JDF-2	34700.0002	120/60	15	2 (12 oz.) drinks/min**	push button	8.7	110 lbs.	Yes
JDF-2	34700.0003	120/60	15	2 (12 oz.) drinks/min**	portion control	8.7	110 lbs.	Yes

Refillable Juice Container Product No.: 33931.0000 Capacity: 1 Gallon

*Models have lighted display ** 75°F AMB, 75°F incoming water

Electrical: Model requires 2-wire grounded service rated 120V, single phase, 60 Hz.

Plumbing: 20-100 psi (138 - 690 kPa). Machine supplied with 3/8" (0.95 cm) male fitting.

Refrigeration: R-134a refrigerant, 10 oz. (.28 kg), 10 lb. (4.6 kg) ice bank system

